



## NSF/ANSI 61 Approvals

Effective 1/1/12

Apollo. Products listed below in Table A meet the permissible lead leaching requirements of **NSF/ANSI 61-Section 8, 2005**.

Series	Sizes	Description	Certifying Lab
64	Up to 4"	Brass Ball Valve	UL

Table A

Apollo Products listed below in Table B meet the full specifications of **NSF/ANSI 61 Section 8 2007B**.

Series	Sizes	Description	Certifying Lab
4C	¼", 3/8"	Carbonated Beverage Backflow	CSA
DC4SG	2-1/2" – 6"	Backflow Preventer	Truesdail
77BLF	Up to 2"	Full Port Side Tap Ball Valve	Truesdail
77W	Up to 2"	Full Port Apollo-Press <sup>®</sup> Ball Valve	Truesdail.
94A	Up to 4"	Brass Ball Valve	Truesdail.

Table B

Apollo Lead Free Products listed below in Table C meet the full specifications of **NSF/ANSI 61 Section 8 2010 Annex F and Annex G**.

Series	Sizes	Description	Certifying Lab
30LF	Up to 3"	Bronze Gate Valve	Truesdail
33LF	Up to 2"	Bronze Globe Valve	Truesdail
34DLF	3/8"	Thermostatic Mixing Valve	Truesdail
36ELF	½" - 1"	Water Pressure Reducing Valve	Truesdail
61LF	Up to 3"	Bronze In-line Check Valve	Truesdail
61YLF	Up to 2"	Bronze Swing Check Valve	Truesdail
70LF	Up to 4"	Standard Port Bronze Ball Valve	Truesdail.
76	Up to 3"	SS Standard Port Ball Valve	Truesdail.
76F	Up to 2"	SS Full Port Ball Valve	Truesdail.
77CLF	Up to 2-1/2"	Full Port Bronze Ball Valve	Truesdail
77WLF	Up to 2"	Full Port Apollo-Press <sup>®</sup> Ball Valve	Truesdail
82LF	Up to 4"	Bronze 3 Piece Ball Valve	Truesdail
86B	Up to 2"	SS 3 Piece Ball Valve	Truesdail.
87A	Up to 4"	SS Full Port Flanged Ball Valve	Truesdail.
94ALF	Up to 4"	Brass Ball Valve	Truesdail
95LF	½" - 1"	Full Port Bronze Drain Ball Valve	Truesdail
Apollo-Push	½"-1"	Threaded Push Connector	Truesdail
Apollo-XPress	½" – 2"	Threaded Press Connector	Truesdail

Table C