



Apollo Valves Lead Free Product Summary December 07, 2011

The products listed below have been certified **“Lead Free**”** by an ANSI approved 3rd party test agency. The wetted surfaces of these products shall contain no more than 0.25% lead by weighted average.

These products meet the requirements of the following State and Federal legislation:

- **Section 116875 of the California Health and Safety Code (commonly referred to as AB-1953)**
- **Vermont Act 193**
- **Maryland HB372 – effective January 1, 2012**
- **Louisiana HB471 – effective January 1, 2013**
- **Federal Public Law 111-380, effective January 4, 2014**

For further information regarding pricing and availability, please contact your local Apollo representative, the factory or our website at www.Apollovalves.com.

Series	Sizes	Description	End connection types
30LF*	1/4" – 3"	Bronze Gate Valve	NPT, Solder, Press
33LF*	1/4" – 2"	Bronze Globe Valve	NPT, Solder, Press
34ALF	1/2" - 1"	Mixing Valve	NPT, Solder, PEX, CPVC
34BLF	1/2" - 1"	Mixing Valve	NPT, Solder, PEX, CPVC
34DLF*	3/8"	Mixing Valve	Compression
36CLF	1/2" - 1"	Water Pressure Reducing Valve	NPT, Solder, PEX, CPVC, Push, Press
36ELF*	1/2" - 1"	Water Pressure Reducing Valve	NPT, Solder, PEX, CPVC, Push, Press
36LF	1/2" - 2"	Water Pressure Reducing Valve	NPT, Solder, PEX, CPVC
36HLF	1/2" - 3"	Water Pressure Reducing Valve	NPT, Flanged
38LF-100	1/4" -2"	Atmospheric Vacuum Breaker	NPT
40LF-000	1/8"	Freeze Protection Valve	NPT
40LF-200**	1 1/4", 1 1/2"	Reduced Pressure Assembly	NPT
40LF-300	1/2" - 1"	Dual Check Valve	NPT, NPSM, BSPP
40LF-400	1/2" - 3/4"	Dual Check with Atmospheric Port	NPT, Solder, BSPP
4ALF-100**	1/2" - 2"	Double Check Valve	NPT
4ALF-100**	2 1/2" - 8"	Double Check Valve	Flanged, Grooved
4ALF-200**	1/2" - 2"	Reduced Pressure Assembly	NPT
4ALF-200**	2-1/2" - 8"	Reduced Pressure Assembly	Flanged, Grooved
4ANLF-100**	2-1/2" - 8"	Double Check Valve	Flanged, Grooved
4ANLF-200**	2-1/2" - 8"	Reduced Pressure Assembly	Flanged, Grooved
4C100	1/4" - 3/8"	Carbonated Beverage Backflow Prev.	NPT & Flare
4FPLF300	1" - 1-1/4"	Residential Dual Check Valve	NPT & NPSM
4NLF300	3/8" - 1"	Dual Check Valve	NPT, NPSM, BSPP
4SGLF100	2-1/2" - 6"	Double Check Valve	Flanged, Grooved
59LF	1/8" - 4"	Strainer, Bronze	NPT, Push, Press
61LF100*	1/4" - 3"	Check valve, Bronze, Ball Cone	NPT
61LF500*	3/8" - 3/4"	Check valve, Bronze, Soft Seat	NPT
61YLF*	1/4" – 2"	Swing Check, Bronze	NPT, Solder, Press

Series	Sizes	Description	End connection types
70LF*	1/4" - 4"	Ball valve, Bronze	NPT & Solder
70LF-HC*	1/2" - 3/4"	Ball valve, Bronze, Hose Cap & Chain	NPT & Solder
77CLF*	1/4" - 2-1/2"	Ball valve, Bronze	NPT & Solder
77WLF*	1/2" - 2"	Ball valve, Bronze	Press ends
77WLF-HC*	1/2" - 3/4"	Ball valve, Bronze, Hose Cap & Chain	Press end
78LF-RV	3/4"	Ball Valve, Thermal Expansion Relief	NPT, Solder, PEX, Push
82LF*	1/4" - 2-1/2"	Ball valve, Bronze, 3 Piece	NPT, Solder / Brazed
94ALF*	1/4" - 4"	Ball valve, Brass – Apollo Int'l	NPT & Solder
95LF*	1/2" - 1"	Ball valve, Bronze, Stop and waste	NPT & Solder

* - Indicates products also certified to ANSI/NSF 61 Section 8 requirements

** - Denotes backflow prevention products that are ASSE approved but undergoing USC, FCCC & HR testing – approvals pending.

Notes:

1.) Push connections available in sizes 1/2" - 1", service limits 200 psi and 200°F maximum. Pushed joints are removable by means of a demounting tool (sold separately).

2.) ApolloXPress connections available in sizes 1/2" - 2", service limits 200 psig and 250°F maximum. -