



4C-100 SERIES CARBONATED BEVERAGE BACKFLOW PREVENTER

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

DESCRIPTION

The Apollo® 4C-100 Series Carbonated Beverage Backflow Preventer (CBBP) is designed to prevent contamination of potable water due to backflow when installed on water distribution lines serving beverage dispensing equipment.

FEATURES

- Compact Design
- Lowest head loss
- Atmospheric vent provides indication of problems
- Integral strainer for equipment protection
- Repairable check assemblies
- Non-metallic body for corrosion resistance



MATERIAL SPECIFICATIONS

Part Name	Material
Body	Acetal
End Cap	Acetal
Strainer	PVC/Stainless Steel
O-ring	Nitrile
Upstream Check Valve	Nitrile/Stainless Steel/Acetal
Downstream Check Valve	EPDM/Stainless Steel

PERFORMANCE RATING


Maximum Supply Pressure 150 psi
Temperature Range 33 °F – 130 °F

APPROVALS

ASSE® 1022, CSA® B64.3.1 and IAPMO® listed

DIMENSIONS (in.)

Size	1/4"	3/8"
A	3.5	3.7



ORDERING INFORMATION

4 C - 1 0 X - 0 1



SIZE _____

SIZE

- 1 - 1/4"
- 2 - 3/8"

Example: 4C-101-01 = 1/4" inlet and outlet flare end connections

FLOW CURVES



Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA; www.apollovalves.com; 704-841-6000

This specification is provided for reference only. Conbraco reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold.